

Installation on hard PE-cables now easier than ever before!



Class A++



The perfect choice also for installation on cold and hard PE cables!

Very low cable insertion force needed

The requested insertion force to insert the cable is extremely low. The cable slides easy and smooth into the connector. In spite of that – the pull strength is extremely good after compression (typical 480N/48 kg).

New CX3 7.0 QuickMount™ connector for RG6 cable

Installing almost any quality connector on a hard PE cable especially under low installation temperatures is a tough job. Cabelcon's engineers have now developed a new CX3 7.0 QuickMount™ connector for RG 6 cables to overcome that problem. It's labelled with a blue coloured label (like the 5.1) – because it's made for the same cable sizes.

The QuickMount technology means that installation can be done "with two fingers". No more hard work and no more unauthorized slicing of the cable jacket or heating the jacket with a lighter to get them on a cold winter's day. Installation is easier than ever before – even for PVC cables, which in between can be difficult too.

Trials are currently in process with several major European operators who are seduced by the easy mounting of the CX3 7.0 Try them and be convinced.

- Easy and safe installation in seconds
- Unique QuickMount™ compression system
- Nitin-6™ plated for excellent corrosion resistance
- One-piece connectors – no loose parts
- Uses standard CX3 compression tools
- Screening Class A++ (30 – 3000 MHz)
- Operational to 3 GHz

Samples can be requested from our customer service.



Technical Data (Typical)

Operational to 3 GHz	
Impedance	75 Ohm
Max. tensile strength (overall)	480N/49 Kg
Shielding 30- 1000 MHz	111 dB
Transfer impedance 5–30 MHz	0.2 mΩ/item
Return loss@1000 MHz	35 dB
Return loss@3000 MHz	32 dB
IMD (3 rd order@2x500mW)	-130dBc
IMD (IP3 value)	+92 dBm
AMP rating	Cable Data

Detailed datasheets are available on request

Ordering Information

F-56-CX3 7.0 QM

99909407